

	9700	7900	7200	59000	5100	V F	S2	4700
ABS	X						X	X
Acetate	X					X	X	X
Acrylic	X			X			X	X
Aluminum (Anodized)				X				
Brass				X				
Butyrate	X					X		X
Cardboard	M		M	M				M
Cardstock - Uncoated	M		M					M
Cardstock - Polycoated	C	X	X					C
Corrugated Board	M		M	M				M
Corrugated Plastics	C	X						
Fiberboard			X	X				
Glass				X				
Leather			X					
Masonite				X				
Metal - Acrylic Coated	C		X	X				C
Metal - Enamel Coated	C		X	X				C
Paper - Coated	X		X	X				X
Paper - Uncoated	M		M					M
PET								
PETG	X						X	X
Polycarbonate	X				X	X	X	X
Polycarbonate (w/adhesive)								
Polyester (print treated)						X	X	
Polyester (top coated)	X		X			X	X	X
Polyethylene HD (treated)	C			X	X			C
Polyethylene LD (treated)					X			
Polyethylene Banner								
Polypropylene (treated)	C	X			X			C
Polystyrene	X						X	X
Static Cling						X	X	M
Tyvek®	M		M					M
Vinyl - Banner	M					X	M	M
Vinyl - Decal	X					X	X	X
Vinyl - Rigid	X					X	X	X
Wood			X	X				



Solvent Screen Inks Reference Chart

S2 System-2 Gloss Vinyl

- Indoor/Outdoor
- Optimum Performance Decal
- High Gloss, Fast Drying
- Great Chemical Resistance

VF Matt Vinyl

- Indoor Only
- Excellent Printability
- Rigid and Flexible Vinyls
- Fast Drying and Non-Blocking
- Can Be Heat Sealed

9700 All Purpose

- Indoor/Outdoor
- Wide Range of Substrates
- High Gloss, Extremely Flexible
- Suitable for Vacuum Forming

7900 Corogloss

- Indoor/Outdoor Short Term
- Correx
- POP & Signage Applications

7200 Lacquer

- Indoor Only
- POP Displays & Book Covers
- Clean, Bright Colors
- Fast Drying

59000 Enamel Plus Gloss

- Indoor/Outdoor
- Hard-To-Adhere-To-Substrates
- Signs & Displays

Versacon® Classic 5100

- Single Part Container Ink

4700 Aquasafe

- Indoor/Outdoor Water-Based
- Wide Range of Substrates
- Good Weather Resistance
- Flexible for Vacuum Forming

5500 Flat Poster

- Indoor Only
- Flat Finish
- Short Term POP Displays
- Poster & Serigraph Applications

6100 Fast Dry Enamel

- Indoor Only
- Hard-To-Adhere-To-Surfaces
- Fiber Drum & Treated Polyethylene
- Excellent Resistance To Soaps & Detergents

8800 Color Vue Membrane

- Indoor/Outdoor - Specifically For:
- Automotive, Membrane Overlay & Appliance Decorating
- Transparent Lens Like Clarity

9600 Polyester

- Indoor/Outdoor
- Designed for untreated polyester films

ADE Epoxy

- 2 Part Catalyst System
- Hard-To-Adhere-To-Surfaces
- Electronic & Industrial Applications
- Outstanding Solvent, Chemical & Abrasion Resistance

	5500	6100	8400	8800		ADE	GV	9600
ABS				X				
Acetate				X			X	
Acrylic		X		X				
Aluminum (Anodized)		X	C			X		
Brass		X	C			X		
Cardboard	X	M						
Cardstock - Uncoated	X							
Cardstock - Polycoated		X						
Corrugated Board	X	M						
Corrugated Plastics			C			X		
Fiberboard		X						
Glass		X				X		
Leather			C					C
Metal - Acrylic Coated		X	C			X		
Metal - Enamel Coated		X	C					
Metal - Polyester Coated			C					
Paper - Coated	X	X						
Paper - Uncoated	X	M						
PET			C					
PETG			C					
Polycarbonate			X	X			X	X
Polycarbonate (w/adhesive)				X				
Polyester (Untreated)								X
Polyester (print treated)			C	X			X	S
Polyester (top coated)			C	X			X	X
Polyethylene HD (treated)		X	C			X		
Polyethylene LD (treated)								
Polyethylene Banner								
Polypropylene (treated)		X				X		
Polypropylene (Untreated)								
Polystyrene								
Static Cling								
Tyvek®								
Vinyl - Banner								
Vinyl - Decal							X	
Vinyl - Rigid							X	
Wood		X						

*Pre-test all recommendations prior to full production. Where noted "X" indicates recommended for testing, "S" indicates some materials, "M" indicates recommended for testing with matte flattener, "C" indicates recommended for testing with appropriate catalyst. When catalyzing solvent-based inks, typically 10% NB72 is used for indoor applications and 10% NB80 is used for outdoor applications. Whenever using a catalyst, allow 24 – 48 hours for inks to fully post-cure before checking adhesion.